

LED Tape Selection Reference Guide

KLUS	COLOR (KELVIN TEMP)	SERIES #	VOLTAGE	PER FOOT			MILLIMETER WIDTH	
				WATTAGE	LUMENS	MAX RUN	IP20	IP65
STANDARD, HIGH CRI (95+) 24V - IP20/65 TAPE								
K or KWP	CR27	1210	24V	1.5	106	32.8/23.9	8	10
	CR30				109			
	CR35				119			
	CR40				118			
K or KWP	CR27	1220	24V	3	204	32.8/23.9	8	10
	CR30				214			
	CR35				233			
	CR40				235			
K or KWP	CR27	1275	24V	4.5	324	32.8/23.9	8	10
	CR30				331			
	CR35				357			
	CR40				372			
HIGH DEFINITION, HIGH CRI (95+) 24V - IP20/65 TAPE								
K or KWP	CRHD27	0530	24V	1.6	117	23.9	10	12
	CRHD30				116			
	CRHD35				137			
	CRHD40				140			
K or KWP	CRHD27	1910	24V	3	247	23.9	10	12
	CRHD30				263			
	CRHD35				272			
	CRHD40				272			
K or KWP	CRHD27	1820	24V	5.6	412	16.4	10	12
	CRHD30				458			
	CRHD35				474			
	CRHD40				487			
HIGH EFFICIENCY, HIGH DEFINITION (CRI 95+) 24V - IP20/65 TAPE								
K or KWP	HEHD27	0480	24V	1.5	138	45.9/23.9	10	12
	HEHD30				144			
	HEHD35				146			
	HEHD40				149			
K or KWP	HEHD27	0960	24V	3	315	23.9	10	12
	HEHD30				326			
	HEHD35				334			
	HEHD40				344			
K or KWP	HEHD27	1440	24V	4.4	460	23.9	10	12
	HEHD30				477			
	HEHD35				504			
	HEHD40				532			
K	HEHD27	1920	24V	5.9	660	20.0	10	-
	HEHD30				676			
	HEHD35				708			
	HEHD40				736			
GEL COATED (CRI 90+) - IP65 TAPE								
KWP	GHD27	0530	24V	1.6	127	23.9	-	10
	GHD30				138			
	GHD35				143			
	GHD40				143			
KWP	GHD27	1910	24V	2.8	250	23.9	-	10
	GHD30				270			
	GHD35				290			
	GHD40				299			
KWP	GHD27	1640	24V	5.0	395	16.4	-	10
	GHD30				441			
	GHD35				458			
	GHD40				472			
RGB/RGB+W TAPE								
K-RGB-0700-120	 R G B		24V	2.13	121	22.75	8	10
K-RGB-1200-120	 R G B		24V	3.66	175	18	8	10
K-RGB-1920-120	 R G B		24V	5.85	191	18	8	10
K-RGBW-1530	 R G B W		24V	4.66	240	19.7	10	12
K-RGBW-1920	 R G B W		24V	5.85	307	16.4	14	16
ADJUSTABLE WHITE TAPE								
K or KWP	27/65	1920	24V	5.8	500	13.2	8	10
K or KWP	22/50	1728	24V	5.8	416	16.4	10	12
DIM TO WARM TAPE								
K or KWP	18/30 MUST USE PWM DIMMER/DRIVER	1770	24V	3.5	318	16.4	10	12
K or KWP	18/30 MUST USE 0-10V DIMMER/DRIVER	1770-010	24V	3.5	292	16.4	10	12

KLUS	COLOR (KELVIN TEMP)	SERIES #	VOLTAGE	PER FOOT			MILLIMETER WIDTH	
				WATTAGE	LUMENS	MAX RUN	IP20	IP65
NEON FLEX MINI (CLEAN LINE LED TAPE) - IP65 FLEXIBLE								
K -NFM	27	0720	24V	2.2	180	16.4	-	6
	30				168			
	35				198			
	40				193			
K-NFM	27	1920	24V	5.9	378	16.4	-	10
	30				344			
	35				435			
	40				418			
SIDE TO SIDE BENDABLE NEON FLEX - IP67 FLEXIBLE								
K -NF	27	0768	24V	2.3	60	49.2	-	10
	30				65			
	35				70			
	40				75			
K-NF	27	1220	24V	2.9	161	49.2	-	12
	30				162			
	35				167			
	40				172			
K-NF-RGB-1730H	R G B		24V	5.3	42	16.4	-	10
UP AND DOWN BENDABLE NEON FLEX - IP67 FLEXIBLE								
K-NF	27	0780	24V	2.4	161	49.2	-	14
	30				125			
	35				175			
	40				126			
K-NF-RGB-1730V	R G B		24V	5.3	154	32.8	-	20
K-NF-RGBW35- 1730V	R G B W		24V	5.3	212	16.4	-	16
TUBULAR NEON FLEX ROUND - IP65 FLEXIBLE								
K-NFR	27	1600	24V	4.9	358	16.4	-	23
	30				384			
	35				398			
	40				395			
K-NFR-RGB-1920	R G B		24V	5.9	217	16.4	-	23
SIDE EMITTING 24V (CRI 90+) - IP20/65 TAPE								
K or KWP	SE27	1210-8	24V	1.5	89	19.7	8	10
	SE30				91			
	SE35				95			
	SE40				96			
K or KWP	SE27	1220-8	24V	3	211	16.4	8	10
	SE30				230			
	SE35				245			
	SE40				245			
K or KWP	SE27	1275-8	24V	4.5	279	13.1	8	10
	SE30				303			
	SE35				297			
	SE40				314			
LINE VOLTAGE (120V) - IP65 TAPE- STATIC WHITE								
KWP	LV27	1213	120V	3.7	315	50.0	-	17
	LV30				330			
	LV35				334			
	LV40				350			
LINE VOLTAGE (120V) - IP65 TAPE - DIM TO WARM								
KWP	LV18D30	1213	120V	3.7	330	50.0	-	17
KWP	LV27D50	1213	120V	3.7	330	50.0	-	17

KLUS LLC

673 US Highway 1
Vero Beach, FL 32962



KLUS LED Fixtures
are proudly made in the USA

Any questions?

orders@klusdesign.com
www.KlusDesign.com

Phone 772-321-2260